

BallastWise®



FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

CATALOG NO.	TYPE	STARTING METHOD	NUMBER OF LAMPS	LAMP TYPE
DXE16H8	Electronic	Instant Start	16	F32T8, F25T8, F17T8 F25T12, F34T12, F40T12 F30T8, F18T8, F15T8

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	REQUENCY	LAMP WATTS	INPUT WATTS	INPUT CURRENT	THD	PF	SOUND RATED A	
120V	60Hz	32W, 25W, 17W 25W, 34W, 40W 30W, 18W, 15W	444W	Max. 4.48A	<30%	0.95		
MIN START TEMP	Class P	TYPE 1 Outdoor	BALLAST FACTOR		BEF	O.C.V.	BALLAST FREQUENCY	NO PCB'S
-20°F/-28.8°C			0.92	0.207	600VRMS	>40kHz		

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS				
	UNITS	M	L	W	H
	INCHES	18.74	19.24	3.44	1.00
TOL(+/-)	0.05	0.05	0.05	0.05	
LEAD LENGTH					
UNITS	BLACK	WHITE	RED	BLUE	
INCHES	CONNECTOR	CONNECTOR	4x36	16x24	
TOL(+/-)	1	1	+3/8,-0	+3/8,-0	

PRODUCT PHOTO

PRODUCT LABEL

	<p>MODEL NO.: 4*DXE4H8 Input: 120V/60Hz Max. Current: 3.80A Power Factor: 0.95 Lamp Type: 16*F32T8, 16*F25T8, 16*F17T8 16*F25T12, 16*F34T12, 16*F40T12 16*F30T8, 16*F18T8, 16*F15T8</p>	<p>Type 1 Outdoor Class P Sound Rating A No PCB's</p>	<p>Instant Start O.C.V.: 600VRMS Start Temp.: -20°F-120°F</p>	<p>1-866-433-9468</p>	<p>LISTED E178684 61FK</p>
--	--	---	--	------------------------------	---

WARNING: Insulate unused lead(s) for 1000V. Install per National and Local Electrical Codes. Ground Ballast & Mount within 3/4" of ground Metal Reflector.
 DATE: _____