

BallastWise®



FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

CATALOG NO.	TYPE	STARTING METHOD	NUMBER OF LAMPS	LAMP TYPE
DXE8H8	Electronic	Instant Start	8	F32T8, F25T8, F17T8 F25T12, F34T12, F40T12 F30T8, F18T8, F15T8

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	REQUENCY	LAMP WATTS	INPUT WATTS	INPUT CURRENT	THD	PF	SOUND RATED A	
120V	60Hz	32W, 25W, 17W 25W, 34W, 40W 30W, 18W, 15W	222W	2.24A	<30%	0.95		
MIN START TEMP	Class P	TYPE 1 Outdoor	BALLAST FACTOR		BEF	O.C.V.	BALLAST FREQUENCY	NO PCB'S
-20°F/-28.8°C			0.92	0.414	600VRMS	>40kHz		

PHYSICAL CHARACTERISTICS

CASE DIMENSIONS					
UNITS	M	L	W	H	
INCHES	18.74	19.24	1.72	1.00	
TOL(+/-)	0.05	0.05	0.05	0.05	
LEAD LENGTH					
UNITS	BLACK	WHITE	RED	BLUE	
INCHES	CONNECTOR	CONNECTOR	2x36	8x24	
TOL(+/-)	1	1	+3/8,-0	+3/8,-0	

PRODUCT PHOTO

PRODUCT LABEL

<p>BallastWise™ ELECTRONIC BALLAST MODEL NO.: 2*DXE4H8</p>	<p>Input: 120V/60Hz Max. Current: 2.24A Power Factor: 0.95 Start Temp.: -20°F ~ 120°F No PCB's</p> <p>Type 1 Outdoor Instant Start Sound Rating A O.C.V.: 600VRMS Class P</p> <p>Lamp Type: 8*F32T8, 8*F25T8, 8*F17T8 8*F25T12, 8*F34T12, 8*F40T12 8*F30T8, 8*F18T8, 8*F15T8</p>	<p>DuroPower 1-866-433-9468</p> <p> LISTED E178684 61FK</p>	<p>WARNING: Insulate unused lead(s) for 1000V. Install per National and Local Electrical Codes. Ground Ballast & Mount within 3/4" of ground Metal Reflector.</p> <p>DATE:</p>
---	--	--	---